

TECHNICAL DATA SHEET

Product Name: Adelaide 50

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	165 x 330 x 50		
Dimensions Imperial (inches):	6.5 x 13 x 2		
Individual Weight Kg:	6.38		
Individual Weight lbs:	14.06		
Pieces per Bundle	252		
Units per Layer	21		
Bundle Weight Kg	1606.5		
Bundle Weight Lbs	3542		
Product Texture:	Smooth, Slip-resistance surface		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒					

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.7

Dynamic Co-efficient of Friction)

Colours	Glacier Creek	Grey
SRI Values	34	35

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information