

TECHNICAL DATA SHEET

Product Name: Ashford

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	330 x 220 x 60	220 x 220 x 60	220 x 110 x 60
Dimensions Imperial (inches):	13 x 8.66 x 2.36	8.66 x 8.66 x 2.36	8.66 x 4.33 x 2.36
Individual Weight Kg:	9.53	6.45	3.10
Individual Weight lbs:	21.01	14.21	6.83
Pieces per Bundle	54	72	54
Units per Layer	6	8	6
Bundle Weight Kg	1156		
Bundle Weight Lbs	2812.00		
Product Texture:	Smooth		

Product Uses:

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
Pedestrian ☒	Vehicular ☒		☒				

Physical Parameters

Dimensional tolerances:

Length: -1.0 to +2.0mm

Width: -1.0 to +2.0mm

Height: -3.0 to +3.0mm

Compressive Strength: 50 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.78

(Dynamic Co-efficient of Friction)

	Colorado	Grey Mix	Summer
Colours	Grey		Mist
SRI Values	41	23	41

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information