

TECHNICAL DATA SHEET

Product Name: Basketweave 12x24
Product Type: Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	300 x 600 x 45		
Dimensions Imperial (inches):	11.81 x 23.62 x 1.57		
Individual Weight Kg:	18.13		
Individual Weight lbs:	40.00		
Pieces per Bundle	72		
Units per Layer	6		
Bundle Weight Kg	1305.4		
Bundle Weight Lbs	2880.0		
Product Texture:	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm
Width: -1.0 to 2.0mm
Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.90

Dynamic Co-efficient of Friction)

Colours White
SRI Values 51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for
3. Pedestal set design should be consulted by project specific engineer

TECHNICAL DATA SHEET

Product Name: Basketweave 24x24

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 45		
Dimensions Imperial (inches):	23.62 x 23.62 x 1.77		
Individual Weight Kg:	38.00		
Individual Weight lbs:	83.80		
Pieces per Bundle	24		
Units per Layer	2		
Bundle Weight Kg	912.0		
Bundle Weight Lbs	2011.2		
Product Texture:	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm
 Width: -1.0 to 2.0mm
 Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
 A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.90

(Dynamic Co-efficient of Friction)

Colours **White**
 SRI Values 51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer
4. These products meet the following design guidelines for accessible paths: Slip-resistance surface

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Basketweave 24x30

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 750 x 45		
Dimensions Imperial (inches):	23.62 x 29.52 x 1.77		
Individual Weight Kg:	48.00		
Individual Weight lbs:	105.82		
Pieces per Bundle	24		
Units per Layer	2		
Bundle Weight Kg	1152.0		
Bundle Weight Lbs	2539.7		
Product Texture:	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

Product Uses:

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm
Width: -1.0 to 2.0mm
Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.90

(Dynamic Co-efficient of Friction)

Colours **White**
SRI Values 51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Basketweave 24x24x50 - Special Order

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 50		
Dimensions Imperial (inches):	23.62 x 23.62 x 2		
Individual Weight Kg:	44.27		
Individual Weight lbs:	92.60		
Pieces per Bundle	20		
Units per Layer	2		
Bundle Weight Kg	885.4		
Bundle Weight Lbs	1852.0		
Product Texture:	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.90

Dynamic Co-efficient of Friction)

Colours **White**
SRI Values 51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Basketweave 24x24x60 - Special Order
Product Type: Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 60		
Dimensions Imperial (inches):	23.62 x 23.62 x 2.36		
Individual Weight Kg:	49.29		
Individual Weight lbs:	108.67		
Pieces per Bundle	18		
Units per Layer	2		
Bundle Weight Kg	887.2		
Bundle Weight Lbs	1956.0		
Product Texture:	Slip-resistant surface, intersecting grid pattern. Slight chamfered edge.		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm
Width: -1.0 to 2.0mm
Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.90

(Dynamic Co-efficient of Friction)

Colours **White**
SRI Values 51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

Please contact your Sales Representative for further product information