

TECHNICAL DATA SHEET

Product Name: EcoFlow Permeable

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	125 x 250 x 80		
Dimensions Imperial (inches):	4.92 x 9.84 x 3.14		
Individual Weight Kg:	5.14		
Individual Weight lbs:	11.33		
Pieces per Bundle	256		
Units per Layer	32		
Bundle Weight Kg	1315.8		
Bundle Weight Lbs	2900.9		
Product Texture:			

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒	☒		☒				☒

Physical Parameters

Dimensional tolerances:

Length: -1.0 to +2.0mm
Width: -1.0 to +2.0mm
Height: +/- 3.0mm

Compressive Strength: 50 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Joint Width: 7mm (9/32")

% Surface Opening: 8.40%

Wet DCOF: 0.86

(Dynamic Co-efficient of Friction)

	Colorado Grey	Grey	Grey Mix
Colours			
SRI Values	41	35	23

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information