

TECHNICAL DATA SHEET

Product Name: Hazelton Block
Product Type: Classic Series

Product Specifications	Width x Height x Depth	Width x Height x Depth	Width x Height x Depth
Dimensions Metric (mm):	300 x 125 x 225		
Dimensions Imperial (inches):	11.81 x 4.92 x 8.55		
Individual Weight Kg:	17.36		
Individual Weight lbs:	38.27		
Pieces per Bundle	60		
Units per Layer	12		
Bundle Weight Kg	1041.5		
Bundle Weight Lbs	2296.00		
Product Texture:			

Product Uses:

Residential	Commerical
☒	☒

Physical Parameters

Dimensional tolerances:

Length: +/- 3.0mm
Width: +/- 3.0mm
Height: +/- 3.0mm

Compressive Strength: 20.7 MPa (min)

Water Absorption: 208 kg/m³
(13 lb/ft³)

Freeze thaw: after 100 cycles 1% (max)
after 150 cycles 1.5% (max)

Notes:

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Hazelton Block
Product Type: Classic Series

Product Specifications	Width x Height x Depth	Width x Height x Depth	Width x Height x Depth
Dimensions Metric (mm):	325 x 125 x 175		
Dimensions Imperial (inches):	12.8 x 4.92 x 6.90		
Individual Weight Kg:	15.50		
Individual Weight lbs:	34.21		
Pieces per Bundle	48		
Units per Layer	16		
Bundle Weight Kg	744		
Bundle Weight Lbs	1642.00		
Product Texture:			

Product Uses:

Residential	Commerical
☒	☒

Physical Parameters

Dimensional tolerances:

Length: +/- 3.0mm
Width: +/- 3.0mm
Height: +/- 3.0mm

Compressive Strength: 20.7 MPa (min)

Water Absorption: 208 kg/m³
(13 lb/ft³)

Freeze thaw: after 100 cycles 1% (max)
after 150 cycles 1.5% (max)

Notes:

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information