

TECHNICAL DATA SHEET

Product Name: Huntington Random
Product Type: Classic Series

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	398 x 597 x 70	398 x 398 x 70	199 x 398 x 70
Dimensions Imperial (inches):	15.67 x 23.5 x 2.75	15.67 x 15.67 x 2.75	7.83 x 15.67 x 2.75
Individual Weight Kg:	37.26	24.95	12.33
Individual Weight lbs:	82.93	55.00	27.19
Pieces per Bundle	16	24	24
Units per Layer	2	3	3
Bundle Weight Kg	1435		
Bundle Weight Lbs	3165		
Product Texture:	Smooth		

Product Uses:

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic		Slab on Pedestal Set	
Pedestrian ☒	Vehicular	☒			Accessibility		Permeable

Physical Parameters

Dimensional tolerances:

Length: -1.0 to +2.0mm
Width: -1.0 to +2.0mm
Height: -3.0 to +3.0mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.61

Dynamic Co-efficient of Friction)

	Colorado	Glacier	Grey		
Colours	Grey	Creek	Mix	Summermist	Winterborn
SRI Values	41	34	23	41	21

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Huntington Rectangle
Product Type: Classic Series

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	199 x 398 x 70		
Dimensions Imperial (inches):	7.83 x 15.67 x 2.75		
Individual Weight Kg:	12.29		
Individual Weight lbs:	27.09		
Pieces per Bundle	120		
Units per Layer	15		
Bundle Weight Kg	1470		
Bundle Weight Lbs	3250		
Product Texture:	Smooth		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒					

Physical Parameters

Dimensional tolerances:

Length: -1.0 to +2.0mm
Width: -1.0 to +2.0mm
Height: -3.0 to +3.0mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.61
(Dynamic Co-efficient of Friction)

Colorado
Colours **Grey** **Summermist**
SRI Values 41 41

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information