

## TECHNICAL DATA SHEET

**Product Name:** Parkwall Column Cap

**Product Type:** Caps

| <b>Product Specifications</b>        | <b>Width x Height x Depth</b> | <b>Width x Height x Depth</b> | <b>Width x Height x Depth</b> |
|--------------------------------------|-------------------------------|-------------------------------|-------------------------------|
| <b>Dimensions Metric (mm):</b>       | 600 x 600 x 75                |                               |                               |
| <b>Dimensions Imperial (inches):</b> | 23.62 x 23.62 x 2.95          |                               |                               |
| <b>Individual Weight Kg:</b>         | 64.63                         |                               |                               |
| <b>Individual Weight lbs:</b>        | 142.50                        |                               |                               |
| <b>Pieces per Bundle</b>             | 16                            |                               |                               |
| <b>Units per Layer</b>               |                               |                               |                               |
| <b>Bundle Weight Kg</b>              | 1034                          |                               |                               |
| <b>Bundle Weight Lbs</b>             | 2280.00                       |                               |                               |
| <b>Product Texture:</b>              |                               |                               |                               |

### Product Uses:

| <b>Residential</b>                  | <b>Commerical</b>                   |
|-------------------------------------|-------------------------------------|
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

### Physical Parameters

#### **Dimensional tolerances:**

Length: +/- 3.0mm

Width: +/- 3.0mm

Height: +/- 3.0mm

**Compressive Strength:** 20.7 MPa (min)

**Water Absorption:** 208 kg/m<sup>3</sup>  
(13 lb/ft<sup>3</sup>)

**Freeze thaw:** after 100 cycles 1% (max)  
after 150 cycles 1.5% (max)

### Notes:

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

***Please contact your Sales Representative for further product information***