

TECHNICAL DATA SHEET

Product Name: Smooth / Shot Blast

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 45		
Dimensions Imperial (inches):	23.62 x 23.62 x 1.77		
Individual Weight Kg:	38.00		
Individual Weight lbs:	83.80		
Pieces per Bundle	24		
Units per Layer	2		
Bundle Weight Kg	912.0		
Bundle Weight Lbs	2011.2		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Colours	Grey	White
SRI Values	35	51

Notes:

1. Meets and exceeds the requirements of the CSA A231.2:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer
4. Due to the light appearance of our White colour, there may be a greater susceptibility to the appearance of stains by foreign elements

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Smooth / Shot Blast

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 50		
Dimensions Imperial (inches):	23.62 x 23.62 x 2		
Individual Weight Kg:	44.27		
Individual Weight lbs:	92.60		
Pieces per Bundle	20		
Units per Layer	2		
Bundle Weight Kg	885.4		
Bundle Weight Lbs	1852.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

PTV Test (Slip Resistances): Passed

Centre Load Point Test: Passed

Colours	Grey	White
SRI Values	35	51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer
4. Due to the light appearance of our White colour, there may be a greater susceptibility to the appearance of stains by foreign elements

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Smooth / Shot Blast

Product Type: Classic Series Slab

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 60		
Dimensions Imperial (inches):	23.62 x 23.62 x 2.36		
Individual Weight Kg:	49.29		
Individual Weight lbs:	108.67		
Pieces per Bundle	18		
Units per Layer	2		
Bundle Weight Kg	887.2		
Bundle Weight Lbs	1956.0		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Colours	Grey	White
SRI Values	35	51

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer
4. Due to the light appearance of our White colour, there may be a greater susceptibility to the appearance of stains by foreign elements

Please contact your Sales Representative for further product information