

## TECHNICAL DATA SHEET

Product Name: **Soho**

| Product Specifications        | Width x Height x Depth | Width x Height x Depth | Width x Height x Depth | Width x Height x Depth |
|-------------------------------|------------------------|------------------------|------------------------|------------------------|
| Dimensions Metric (mm):       | 350 x 100 x 225        | 450 x 100 x 225        | 550 x 100 x 225        | 650 x 100 x 225        |
| Dimensions Imperial (inches): | 13.78 x 3.94 x 8.85    | 17.72 x 3.94 x 8.85    | 21.65 x 3.94 x 8.85    | 25.59 x 3.94 x 8.85    |
| Weight per 4 pack Kg:         | 97.00                  |                        |                        |                        |
| Weight per 4 pack lbs:        | 214.00                 |                        |                        |                        |
| Pieces per Bundle             | 9                      | 9                      | 9                      | 9                      |
| Units per Layer               | 3                      | 3                      | 3                      | 3                      |
| Bundle Weight Kg              | 873.6                  |                        |                        |                        |
| Bundle Weight Lbs             | 1926.00                |                        |                        |                        |
| Product Texture:              |                        |                        |                        |                        |

### Product Uses:

| Residential                         | Commerical                          |
|-------------------------------------|-------------------------------------|
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

### Physical Parameters

#### Dimensional tolerances:

Length: +/- 3.0mm

Width: +/- 3.0mm

Height: +/- 3.0mm

Compressive Strength: 20.7 MPa (min)

Water Absorption: 208 kg/m<sup>3</sup>  
(13 lb/ft<sup>3</sup>)

Freeze thaw: after 100 cycles 1% (max)  
after 150 cycles 1.5% (max)

| Colours    | Carrara | Glacier<br>Creek | Grey Mix |
|------------|---------|------------------|----------|
| SRI Values | 30      | 34               | 23       |

### Notes:

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

***Please contact your Sales Representative for further product information***

## TECHNICAL DATA SHEET

**Product Name:** Soho Corner  
**Product Type:** Signature Series

| <u>Product Specifications</u>        | Width x Height x Depth | Width x Height x Depth | Width x Height x Depth |
|--------------------------------------|------------------------|------------------------|------------------------|
| <b>Dimensions Metric (mm):</b>       | 350 x 100 x 225        |                        |                        |
| <b>Dimensions Imperial (inches):</b> | 13.78 x 3.94 x 8.85    |                        |                        |
| <b>Individual Weight Kg:</b>         | 16.60                  |                        |                        |
| <b>Individual Weight lbs:</b>        | 36.60                  |                        |                        |
| <b>Pieces per Bundle</b>             | 60                     |                        |                        |
| <b>Units per Layer</b>               | 20                     |                        |                        |
| <b>Bundle Weight Kg</b>              | 996.00                 |                        |                        |
| <b>Bundle Weight Lbs</b>             | 2196.00                |                        |                        |
| <b>Product Texture:</b>              |                        |                        |                        |

### Product Uses:

| Residential                         | Commerical                          |
|-------------------------------------|-------------------------------------|
| <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |

### Physical Parameters

#### Dimensional tolerances:

Length: +/- 3.0mm  
Width: +/- 3.0mm  
Height: +/- 3.0mm

**Compressive Strength:** 20.7 MPa (min)

**Water Absorption:** 208 kg/m<sup>3</sup>  
(13 lb/ft<sup>3</sup>)

**Freeze thaw:** after 100 cycles 1% (max)  
after 150 cycles 1.5% (max)

| Colours           | Carrara | Glacier<br>Creek | Grey Mix |
|-------------------|---------|------------------|----------|
| <b>SRI Values</b> | 30      | 34               | 23       |

### Notes:

1. Meets the requirments for ASTM C1372 - Standard Specifications for Segmental Retaining Wall Units
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

*Please contact your Sales Representative for further product information*