

TECHNICAL DATA SHEET

Product Name: Standard Press 12x24

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	300 x 600 x 45		
Dimensions Imperial (inches):	11.81 x 23.62 x 1.77		
Individual Weight Kg:	18.13		
Individual Weight lbs:	39.97		
Pieces per Bundle	48		
Units per Layer	4		
Bundle Weight Kg	870.2		
Bundle Weight Lbs	1918.5		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or

A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.67

(Dynamic Co-efficient of Friction)

Colours Grey

SRI Values 35

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for
3. Pedestal set design should be consulted by project specific engineer

TECHNICAL DATA SHEET

Product Name: Standard Press 16x16

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	400 x 400 x 45		
Dimensions Imperial (inches):	15.75 x 15.75 x 1.75		
Individual Weight Kg:	15.65		
Individual Weight lbs:	34.50		
Pieces per Bundle	60		
Units per Layer			
Bundle Weight Kg	939.0		
Bundle Weight Lbs	2070.0		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm
Width: -1.0 to 2.0mm
Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.67

Dynamic Co-efficient of Friction)

Colours	Grey	Red
SRI Values	35	26

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Standard Press 24x24

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 600 x 45		
Dimensions Imperial (inches):	23.62 x 23.62 x 1.77		
Individual Weight Kg:	38.00		
Individual Weight lbs:	83.80		
Pieces per Bundle	24		
Units per Layer	2		
Bundle Weight Kg	912.0		
Bundle Weight Lbs	2011.2		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic		Slab on Pedestal Set	
Pedestrian	Vehicular				Accessibility		Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.67

Dynamic Co-efficient of Friction)

Colours	Grey	Red
SRI Values	35	26

Notes:

1. Meets the requirements of CSA A231.1:19 Precast concrete patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.
3. Pedestal set design should be consulted by project specific engineer

Please contact your Sales Representative for further product information

TECHNICAL DATA SHEET

Product Name: Standard Press 24x30
Product Type: Classic Series Slab

Product Specifications	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	600 x 750 x 45		
Dimensions Imperial (inches):	23.62 x 29.52 x 1.77		
Individual Weight Kg:	48.00		
Individual Weight lbs:	105.82		
Pieces per Bundle	24		
Units per Layer	2		
Bundle Weight Kg	1152.0		
Bundle Weight Lbs	2539.7		
Product Texture:	Slip-resistant surface		

Product Uses:

Residential	Commerical				Other		
		Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒				☒	

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.67

Dynamic Co-efficient of Friction)

Colours Grey
SRI Values 35

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for
3. Pedestal set design should be consulted by project specific engineer