

TECHNICAL DATA SHEET

Product Name: Trevista 50 Textured

<u>Product Specifications</u>	Length x Width x Height	Length x Width x Height	Length x Width x Height
Dimensions Metric (mm):	495 x 330 x 50	330 x 330 x 50	165 x 330 x 50
Dimensions Imperial (inches):	19.5 x 13 x 2	13 x 13 x 2	6.5 x 13 x 2
Individual Weight Kg:	18.87	12.27	6.02
Individual Weight lbs:	41.60	27.05	13.27
Pieces per Bundle	24	48	48
Units per Layer	2	4	4
Bundle Weight Kg	1365		
Bundle Weight Lbs	3010		

Product Uses:

Residential	Commerical				Other		
Pedestrian	Vehicular	Pedestrian only	Pedestrian & Vehicular	Vehicular Traffic	Accessibility	Slab on Pedestal Set	Permeable
☒		☒					

Physical Parameters

Dimensional tolerances:

Length: -1.0 to 2.0mm

Width: -1.0 to 2.0mm

Height: +/- 3.00mm

Flexural Strength: 5.0 MPa (min)

Freeze thaw: A maximum of 225g/m² loss of mass after 28 cycles of freezing and thawing or
A maximum of 500g/m² loss of mass after 49 cycles of freezing and thawing

Wet DCOF: 0.66

(Dynamic Co-efficient of Friction)

Colours	Autumn Hill	Carrara	Glacier Creek	Grey Mix
SRI Values	38	30	34	23

Notes:

1. Meets and exceeds the requirements of the CSA A231.1:19 Precast concrete pavers and patio slabs.
2. All data within this document is for reference purpose only and provided as such. Independent engineering should be used for complete site-specific accuracy in all projects.

Please contact your Sales Representative for further product information